

# Doors of Distinction - Pre-Glazed Hardwood Exterior Doors and Sidelights

## EXTERIOR DOOR SPECIFICATIONS

**Meranti Hardwood** 44mm thick and Mortice & Tenon Construction and supplied unstained for on site finishing. The pre-glazed doors generally feature decorative raised mouldings around the panels and the glazing apertures on one side only. Colours of the timber vary from dull beige to red-brown, but are colour matched as near as possible within each door. Suitable for light to dark colour staining with 'SIKKENS' products, or painting using suitable primer, please ask for instructions at time of ordering

**Oak** Exterior Doors are manufactured using an engineered construction to give extra stability. Each door has Raised Mouldings to both sides (in some designs front of door only) and incorporate brass camings as described below.

Stiles and Head Rail are generally approx. 125mm (Ex 5") and panels are Raised and Fielded on both sides and sealed in with mastic.

**Pre-glazed Doors:** are manufactured with traditional hand made lead lights, (some available brass or zinc came), with clear bevelled glass, cracked ice glass and cloured lights in some designs, which are sandwiched between two pieces of toughened glass, giving a Triple glazed unit to facilitate safety, security and ease of cleaning. Due to traditional methods of construction of glazing, a small amount of rattling in the glass can occur occasionally. This is not considered a defect.. Photographic reproduction depends on which background the doors were photographed. Timber colour depends on whether the door in the photograph is natural or has been stained.

\*Doors may contain stiles and rails engineered from composite or laminated materials with laminated face veneers

## ESSENTIAL DOOR CARE

### Fitting Advice:

- Reduce doors to fit equally from both sides, but not excessively, e.g. maximum of 6mm from each side.
- Seal the door with two coats of 'Sikkens HLS' before first fix, then taking off all ironmongery coat every surface liberally with a minimum of 3 coats of 'Sikkens Filter 7', including all cut outs, before refitting.
- The number of coats advised by the manufacturer is usually a minimum, it is therefore wise to exceed this if possible.
- Fully seal glass rebates and backs of glazing beads prior to glazing on models supplied without glass.
- Never fit mortice locks etc. at rail joints as this may seriously weaken them. and use a minimum of three 4" hinges.
- Always fit with suitable weatherboard regardless of frame cill type fitted, to prevent droplets of moisture hanging from the bottom of the door.

## Door Sizes

Metric	Imperial
762mm x 1981mm	30" x 78"
813mm x 2032mm	32" x 80"
838mm x 1981mm	33" x 78"
864mm x 2083mm	34" x 82"
914mm x 1981mm	36" x 78"
914mm x 2134mm	36" x 84"
1067mm x 1981mm	42" x 78"
1117mm x 1981mm	44" x 78"
1168mm x 1981mm	46" x 78"
1220mm x 1981mm	48" x 78"
1372mm x 1981mm	54" x 78"
1524mm x 1981mm	60" x 78"

## Sidelight Sizes

Metric	Imperial
381mm x 1981mm	15" x 78"
406mm x 1981mm	16" x 78"
406mm x 2032mm	16" x 80"
406mm x 2083mm	16" x 82"
457mm x 1981mm	18" x 78"
457mm x 2057mm	18" x 81"
584mm x 2040mm	23" x 80"

Sidelights are specifically made for cutting to size:

A maximum of 60mm off each side and top edges, as long as they are a fixed feature

e.g. (non opening sidelight)

Please consult web site for latest availability on sizes:

[www.doorsofdistinction.co.uk](http://www.doorsofdistinction.co.uk)

## IMPORTANT

Re-coat your door every 2-3 years depending on wear and tear that can be observed.

It is also important to protect your door from direct sunlight and rain by means of a porch, canopy or similar construction

WE CANNOT REPLACE A FAULTY DOOR AFTER ALTERATIONS HAVE BEEN CARRIED OUT.

MORE INFORMATION AVAILABLE ON THE BACK OF YOUR INVOICE

## Oak & Hardwood Door Frame Kits -All including Frame seal and Water bar



Single Door Frames Door size quoted	Aproximate Overall Frame size
30" x 78" - 762mm x 1981mm...	854mm x 2067mm
32" x 80" - 813mm x 2032mm...	905mm x 2118mm
33" x 78" - 838mm x 1981mm....	930mm x 2067mm
34" x 82" - 864mm x 2083mm....	960mm x 2168mm
36" x 84" - 914mm x 2134mm....	1003mm x 2220mm

Double Door Frames Door size quoted	Aproximate Overall Frame size
36" x 78" - 915mm x 1981mm ....	1007mm x 2067mm
42" x 78" - 1067mm x 1981mm....	1155mm x 2067mm
46" x 78" - 1168mm x 1981mm....	1256mm x 2067mm
48" x 78" - 1220mm x 1981mm....	1308mm x 2067mm
54" x 78" - 1372mm x 1981mm....	1460mm x 2067mm
60" x 78" - 1524mm x 1981mm....	1612mm x 2067mm



Single Door & Sidelight Frames Door size quoted	Sidelight Size	Aproximate Overall Frame size (width x height)
32" x 80" - 813mm x 2032mm.....	23" - 584mm x 2032mm.....	2179mm x 2118mm
33" x 78" - 838mm x 1981mm.....	23" - 584mm x 2032mm.....	2179mm x 2067mm
33" x 78" - 838mm x 1981mm.....	18" - 457mm x 1981mm.....	1912mm x 2067mm

Please Note: Sidelights are specifically made for cutting to size:

A maximum of 60mm off each side and top edges, as long as they are a fixed feature e.g. (non opening sidelight)

To accommodate narrower sidelights, the side mullions can be re-positioned on the frame

Please consult web site for latest availability on sizes:

Dorset Branch: 63 Cobham Rd - Ferndown Industrial Estate - Ferndown - Dorset - BH21 7QF  
e-mail - [dorset@doorsofdistinction.co.uk](mailto:dorset@doorsofdistinction.co.uk) - Tel 01202 872211

Devon Branch: 1 The Old Sawmills - Hawkerland Road - Colaton Raleigh - Sidmouth - Devon - EX10 0BH  
e-mail - [devon@doorsofdistinction.co.uk](mailto:devon@doorsofdistinction.co.uk) - Tel 01395 568400